

MATRIX SETU VFXTH vs AUDIOCODES MP Series

Matrix ComSec

Description	MATRIX	AUDIOCODES
Model	SETU VFXTH	MP-124
Product Photograph		
Dimensions	51 x 407 x 172 mm	44 x 445 x 269 mm
Configuration		
VoIP Channels	Up to 32	24
VoIP Port Connector	RJ45	RJ45
FXS Ports	Up to 32 Ports	24 Ports
FXO Port	Up to 32 Ports	NA
FXS/FXO Connector	RJ11	50-Pin Telco Connector
Indicators	Channel Status & Activity LEDs	Channel Status & Activity LEDs
Protocols	SIP, DHCP, TFTP, SNMP, STUN	SIP, DHCP, TFTP, SNMP
Codecs	G.711 a/u, G.729ab, G.723,	G.711, G.723.1, G.726, G.729A
Simultaneous Calls	Up to 32	24
Fallback	PSTN	PSTN
Stand Alone Survivability	YES	YES
Features		
Access Codes	YES	-
Allowed and Denied List	YES	YES
Automatic Number Translation	YES	YES
Call Transfer	YES	YES
Call Progress Tones/Rings	YES	YES
Conference	YES	YES
Call Back	YES	-
Fax over IP (FoIP)	T.38	T.38
Incoming Call Routing	YES	-
Web based configuration	YES	YES
Remote configuration	YES	YES
VLAN QoS	DiffServ, TOS	DiffServ, TOS
VLAN Tagging	YES	YES
Syslog Support	YES	YES
Physical		
Power	24 VDC, 2.5A	100-240 VAC, 50-60Hz or -48VDC
Mounting	Rack, Table-top, Wall	Rack, Table-top, Wall
Overvoltage and Surge protection	YES	YES